



SPACESAVER™ SYSTEMS

AVR95 DISCHARGE RATES IN WATTS PER CELL

Ratings in Watts per cell at 77°F (25°C) to 1.60 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	863.9	755.4	662.2	595.8	543.7	460.6	316.5	244.5	201.8	151.2	121.7	102.7	89.3	79.3	71.5	65.2	60.0	52.0	41.3	34.4	29.5	16.1	11.2	8.23
AVR95-9	1151.9	1007.2	882.9	794.4	725.0	614.2	422.0	326.0	269.1	201.6	162.3	136.9	119.1	105.7	95.3	86.9	80.0	69.3	55.1	45.8	39.3	21.5	14.9	11.0
AVR95-11	1439.9	1259.0	1103.6	993.0	906.2	767.7	527.5	407.5	336.4	252.0	202.9	171.1	148.8	132.2	119.1	108.6	100.0	86.7	68.9	57.3	49.1	26.9	18.6	13.7
AVR95-13	1727.8	1510.8	1324.3	1191.6	1087.4	921.3	633.0	489.0	403.6	302.4	243.5	205.3	178.6	158.6	142.9	130.4	120.0	104.0	82.6	68.7	58.9	32.3	22.4	16.5
AVR95-15	2015.8	1762.6	1545.1	1390.2	1268.7	1074.8	738.5	570.6	470.9	352.8	284.1	239.6	208.4	185.0	166.8	152.1	140.0	121.3	96.4	80.2	68.7	37.6	26.1	19.2
AVR95-17	2303.8	2014.4	1765.8	1588.8	1449.9	1228.3	844.0	652.1	538.2	403.2	324.6	273.8	238.2	211.5	190.6	173.8	160.0	138.7	110.2	91.7	78.6	43.0	29.8	22.0
AVR95-19	2591.7	2266.2	1986.5	1787.4	1631.1	1381.9	949.5	733.6	605.4	453.6	365.2	308.0	267.9	237.9	214.4	195.5	180.0	156.0	123.9	103.1	88.4	48.4	33.6	24.7
AVR95-21	2879.7	2518.0	2207.2	1986.0	1812.4	1535.4	1055.0	815.1	672.7	504.0	405.8	342.2	297.7	264.3	238.2	217.3	200.0	173.3	137.7	114.6	98.2	53.8	37.3	27.4
AVR95-23	3167.7	2769.8	2427.9	2184.6	1993.6	1689.0	1160.5	896.6	740.0	554.4	446.4	376.5	327.5	290.8	262.0	239.0	220.0	190.7	151.5	126.0	108.0	59.1	41.0	30.2
AVR95-25	3455.6	3021.6	2648.7	2383.2	2174.9	1842.5	1266.0	978.1	807.3	604.8	487.0	410.7	357.2	317.2	285.9	260.7	240.0	208.0	165.2	137.5	117.8	64.5	44.7	32.9
AVR95-27	3743.6	3273.4	2869.4	2581.8	2356.1	1996.0	1371.5	1059.6	874.5	655.2	527.5	444.9	387.0	343.6	309.7	282.4	260.0	225.3	179.0	148.9	127.6	69.9	48.5	35.7
AVR95-29	4031.6	3525.2	3090.1	2780.4	2537.3	2149.6	1477.1	1141.1	941.8	705.6	568.1	479.1	416.8	370.1	333.5	304.2	280.0	242.7	192.8	160.4	137.5	75.3	52.2	38.4
AVR95-31	4319.6	3777.0	3310.8	2979.0	2718.6	2303.1	1582.6	1222.6	1009.1	756.0	608.7	513.3	446.5	396.5	357.3	325.9	300.0	260.0	206.6	171.8	147.3	80.7	55.9	41.2
AVR95-33	4607.5	4028.9	3531.5	3177.6	2899.8	2456.7	1688.1	1304.1	1076.4	806.4	649.3	547.6	476.3	422.9	381.1	347.6	320.0	277.3	220.3	183.3	157.1	86.0	59.7	43.9

Ratings in Watts per cell at 77°F (25°C) to 1.63 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	829.1	727.9	640.6	577.6	528.4	451.6	312.0	243.2	199.9	150.8	121.4	102.5	89.1	79.2	71.3	65.0	59.9	51.9	41.2	34.3	29.4	16.1	11.2	8.22
AVR95-9	1105.5	970.5	854.1	770.1	704.5	602.1	416.0	324.3	266.5	201.0	161.9	136.6	118.9	105.5	95.1	86.7	79.8	69.1	54.9	45.7	39.2	21.5	14.9	11.0
AVR95-11	1381.9	1213.2	1067.6	962.6	880.6	752.6	520.0	405.4	333.2	251.3	202.4	170.8	148.6	131.9	118.9	108.4	99.8	86.4	68.7	57.1	49.0	26.8	18.6	13.7
AVR95-13	1658.3	1455.8	1281.1	1155.2	1056.8	903.2	624.0	486.4	399.8	301.5	242.9	205.0	178.3	158.3	142.6	130.1	119.8	103.7	82.4	68.6	58.8	32.2	22.3	16.4
AVR95-15	1934.6	1698.4	1494.6	1347.7	1232.9	1053.7	728.0	567.5	466.4	351.8	283.3	239.1	208.0	184.7	166.4	151.7	139.7	121.0	96.1	80.0	68.5	37.6	26.1	19.2
AVR95-17	2211.0	1941.1	1708.1	1540.2	1409.0	1204.2	832.0	648.6	533.1	402.1	323.8	273.3	237.7	211.1	190.2	173.4	159.7	138.3	109.9	91.4	78.3	42.9	29.8	21.9
AVR95-19	2487.4	2183.7	1921.7	1732.8	1585.1	1354.7	936.0	729.7	599.7	452.3	364.3	307.4	267.4	237.5	213.9	195.1	179.6	155.6	123.6	102.8	88.1	48.3	33.5	24.7
AVR95-21	2763.8	2426.3	2135.2	1925.3	1761.3	1505.3	1040.0	810.7	666.3	502.6	404.8	341.6	297.2	263.9	237.7	216.8	199.6	172.9	137.3	114.3	97.9	53.7	37.2	27.4
AVR95-23	3040.1	2669.0	2348.7	2117.8	1937.4	1655.8	1144.0	891.8	732.9	552.8	445.2	375.8	326.9	290.2	261.5	238.4	219.6	190.1	151.1	125.7	107.7	59.1	41.0	30.2
AVR95-25	3316.5	2911.6	2562.2	2310.4	2113.5	1806.3	1248.0	972.9	799.6	603.1	485.7	409.9	356.6	316.6	285.2	260.1	239.5	207.4	164.8	137.1	117.5	64.4	44.7	32.9
AVR95-27	3592.9	3154.2	2775.7	2502.9	2289.6	1956.9	1352.0	1053.9	866.2	653.3	526.2	444.1	386.3	343.0	309.0	281.8	259.5	224.7	178.5	148.6	127.3	69.8	48.4	35.6
AVR95-29	3869.3	3396.9	2989.2	2695.4	2465.8	2107.4	1456.0	1135.0	932.8	703.6	566.7	478.2	416.0	369.4	332.8	303.5	279.4	242.0	192.3	160.0	137.1	75.2	52.1	38.4
AVR95-31	4145.6	3639.5	3202.8	2887.9	2641.9	2257.9	1560.0	1216.1	999.5	753.9	607.1	512.4	445.7	395.8	356.6	325.2	299.4	259.3	206.0	171.4	146.9	80.5	55.8	41.1
AVR95-33	4422.0	3882.1	3416.3	3080.5	2818.0	2408.4	1664.0	1297.2	1066.1	804.1	647.6	546.6	475.5	422.2	380.3	346.8	319.4	276.6	219.7	182.8	156.7	85.9	59.6	43.9

Ratings in Watts per cell at 77°F (25°C) to 1.67 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	740.1	676.1	609.1	554.1	508.9	438.7	309.0	241.4	200.0	150.1	121.1	102.2	89.0	79.0	71.2	64.9	59.7	51.7	41.1	34.2	29.3	16.1	11.2	8.21
AVR95-9	986.8	901.5	812.1	738.8	678.6	585.0	412.0	321.9	266.7	200.2	161.5	136.3	118.6	105.3	94.9	86.5	79.7	69.0	54.8	45.6	39.1	21.4	14.9	10.9
AVR95-11	1233.4	1126.8	1015.2	923.5	848.2	731.2	515.0	402.4	333.4	250.2	201.9	170.4	148.3	131.7	118.6	108.1	99.6	86.2	68.5	57.0	48.8	26.8	18.6	13.7
AVR95-13	1480.1	1352.2	1218.2	1108.2	1017.9	877.4	618.0	482.8	400.1	300.2	242.3	204.5	177.9	158.0	142.4	129.8	119.5	103.5	82.2	68.4	58.6	32.1	22.3	16.4
AVR95-15	1726.8	1577.6	1412.2	1292.9	1187.5	1023.7	721.0	563.3	466.8	350.3	282.6	238.5	207.6	184.3	166.1	151.4	139.4	120.7	95.9	79.8	68.4	37.5	26.0	19.2
AVR95-17	1973.5	1802.9	1624.2	1477.6	1357.2	1169.9	824.0	643.8	533.4	400.3	323.0	272.6	237.2	210.7	189.8	173.0	159.3	138.0	109.6	91.1	78.1	42.8	29.7	21.9
AVR95-19	2220.2	2028.3	1827.3	1662.3	1526.8	1316.2	927.0	724.2	600.1	450.4	363.4	306.7	266.9	237.0	213.5	194.6	179.2	155.2	123.3	102.5	87.9	48.2	33.5	24.6
AVR95-21	2466.9	2253.7	2030.3	1847.0	1696.5	1462.4	1030.0	804.7	666.8	500.4	403.8	340.8	296.5	263.3	237.3	216.3	199.1	172.5	137.0	113.9	97.7	53.6	37.2	27.4
AVR95-23	2713.6	2479.1	2233.3	2031.6	1866.1	1608.7	1133.0	885.2	733.5	550.4	444.2	374.8	326.2	289.7	261.0	237.9	219.1	189.7	150.6	125.3	107.4	58.9	40.9	30.1
AVR95-25	2960.3	2704.4	2436.4	2216.3	2035.8	1754.9	1236.1	965.7	800.2	600.5	484.5	408.9	355.8	316.0	284.7	259.5	239.0	207.0	164.3	136.7	117.2	64.3	44.6	32.8
AVR95-27	3206.9	2929.8	2639.4	2401.0	2205.4	1901.1	1339.1	1046.1	866.9	650.5	524.9	443.0	385.5	342.3	308.4	281.2	258.9	224.2	178.0	148.1	127.0	69.6	48.3	35.6
AVR95-29	3453.6	3155.2	2842.4	2585.7	2375.1	2047.4	1442.1	1126.6	933.5	700.6	565.3	477.1	415.1	368.6	332.2	302.8	278.8	241.5	191.7	159.5	136.7	75.0	52.0	38.3
AVR95-31	3700.3	3380.5	3045.5	2770.4	2544.7	2193.6	1545.1	1207.1	1000.2	750.6	605.7	511.2	444.8	395.0	355.9	324.4	298.7	258.7	205.4	170.9	146.5	80.3	55.8	41.1
AVR95-33	3947.0	3605.9	3248.5	2955.1	2714.4	2339.9	1648.1	1287.5	1066.9	800.7	646.0	545.2	474.4	421.3	379.6	346.0	318.6	276.0	219.1	182.3	156.3	85.7	59.5	43.8



SPACESAVERS™ SYSTEMS

AVR95 DISCHARGE RATES IN WATTS PER CELL (cont.)

Ratings in Watts per cell at 77°F (25°C) to 1.70 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	715.6	648.1	583.9	530.3	489.7	424.2	303.2	239.8	198.7	149.7	120.9	102.1	88.8	78.9	71.1	64.8	59.7	51.7	41.1	34.1	29.3	16.1	11.1	8.20
AVR95-9	954.1	864.2	778.5	707.1	652.9	565.6	404.3	319.8	264.9	199.6	161.2	136.1	118.3	105.2	94.8	86.4	79.6	68.9	54.7	45.5	39.0	21.4	14.9	10.9
AVR95-11	1192.7	1080.2	973.2	883.9	816.1	707.0	505.4	399.7	331.1	249.5	201.5	170.1	147.9	131.4	118.4	108.0	99.5	86.2	68.4	56.9	48.8	26.8	18.6	13.7
AVR95-13	1431.2	1296.2	1167.8	1060.7	979.3	848.4	606.4	479.6	397.4	299.4	241.8	204.1	177.5	157.7	142.1	129.6	119.4	103.4	82.1	68.3	58.5	32.1	22.3	16.4
AVR95-15	1669.7	1512.3	1362.4	1237.5	1142.5	989.8	707.5	559.6	463.6	349.3	282.1	238.2	207.1	184.0	165.8	151.2	139.2	120.6	95.8	79.7	68.3	37.5	26.0	19.1
AVR95-17	1908.3	1728.3	1557.1	1414.3	1305.8	1131.2	808.6	639.5	529.8	399.2	322.4	272.2	236.7	210.3	189.5	172.8	159.1	137.9	109.5	91.0	78.0	42.8	29.7	21.9
AVR95-19	2146.8	1944.3	1751.7	1591.0	1469.0	1272.6	909.6	719.5	596.1	449.0	362.7	306.2	266.3	236.6	213.2	194.4	179.0	155.1	123.2	102.4	87.8	48.2	33.4	24.6
AVR95-21	2385.3	2160.4	1946.4	1767.8	1632.2	1414.0	1010.7	799.4	662.3	498.9	402.9	340.2	295.8	262.9	236.9	216.1	198.9	172.3	136.8	113.8	97.5	53.5	37.1	27.3
AVR95-23	2623.9	2376.4	2141.0	1944.6	1795.4	1555.4	1111.8	879.3	728.5	548.8	443.2	374.2	325.4	289.2	260.6	237.7	218.8	189.6	150.5	125.2	107.3	58.9	40.8	30.1
AVR95-25	2862.4	2592.5	2335.6	2121.4	1958.6	1696.8	1212.9	959.3	794.7	598.7	483.5	408.3	355.0	315.5	284.3	259.3	238.7	206.8	164.2	136.6	117.0	64.2	44.6	32.8
AVR95-27	3100.9	2808.5	2530.3	2298.2	2121.9	1838.2	1313.9	1039.2	861.0	648.6	523.8	442.3	384.6	341.8	307.9	280.9	258.6	224.0	177.9	147.9	126.8	69.6	48.3	35.5
AVR95-29	3339.5	3024.5	2724.9	2475.0	2285.1	1979.6	1415.0	1119.2	927.2	698.5	564.1	476.3	414.2	368.0	331.6	302.5	278.5	241.3	191.6	159.3	136.5	74.9	52.0	38.3
AVR95-31	3578.0	3240.6	2919.5	2651.7	2448.3	2121.0	1516.1	1199.1	993.4	748.4	604.4	510.3	443.8	394.3	355.3	324.1	298.4	258.5	205.3	170.7	146.3	80.3	55.7	41.0
AVR95-33	3816.5	3456.6	3114.2	2828.5	2611.5	2262.4	1617.2	1279.0	1059.7	798.3	644.7	544.4	473.3	420.6	379.0	345.7	318.3	275.7	218.9	182.1	156.1	85.6	59.4	43.7

Ratings in Watts per cell at 77°F (25°C) to 1.75 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	636.7	581.4	532.8	491.2	456.3	399.9	294.3	234.4	195.8	148.5	120.2	101.6	88.5	78.6	70.9	64.6	59.5	51.6	41.0	34.1	29.2	16.0	11.1	8.18
AVR95-9	848.9	775.2	710.4	655.0	608.4	533.2	392.4	312.5	261.1	198.0	160.3	135.5	118.0	104.8	94.5	86.2	79.4	68.8	54.6	45.4	38.9	21.3	14.8	10.9
AVR95-11	1061.1	969.0	888.1	818.7	760.5	666.4	490.5	390.6	326.3	247.4	200.4	169.4	147.4	131.0	118.1	107.7	99.2	86.0	68.3	56.8	48.7	26.7	18.5	13.6
AVR95-13	1273.3	1162.8	1065.7	982.5	912.6	799.7	588.6	468.7	391.6	296.9	240.4	203.3	176.9	157.3	141.8	129.3	119.1	103.2	81.9	68.2	58.4	32.0	22.2	16.4
AVR95-15	1485.5	1356.6	1243.3	1146.2	1064.6	933.0	686.6	546.9	456.9	346.4	280.5	237.1	206.4	183.5	165.4	150.8	138.9	120.4	95.6	79.5	68.1	37.4	25.9	19.1
AVR95-17	1697.8	1550.4	1420.9	1310.0	1216.7	1066.3	784.7	625.0	522.2	395.9	320.6	271.0	235.9	209.7	189.0	172.4	158.7	137.6	109.2	90.9	77.9	42.7	29.6	21.8
AVR95-19	1910.0	1744.2	1598.5	1473.7	1368.8	1199.6	882.8	703.1	587.4	445.4	360.7	304.9	265.4	235.9	212.7	193.9	178.6	154.8	122.9	102.2	87.6	48.0	33.3	24.5
AVR95-21	2122.2	1938.0	1776.1	1637.5	1520.9	1332.9	980.9	781.2	652.7	494.9	400.7	338.8	294.9	262.1	236.3	215.5	198.4	172.0	136.5	113.6	97.3	53.4	37.0	27.3
AVR95-23	2334.4	2131.8	1953.7	1801.2	1673.0	1466.2	1079.0	859.4	718.0	544.4	440.8	372.7	324.4	288.3	259.9	237.0	218.3	189.2	150.2	124.9	107.1	58.7	40.7	30.0
AVR95-25	2546.6	2325.6	2131.3	1965.0	1825.1	1599.5	1177.1	937.5	783.2	593.9	480.9	406.5	353.9	314.5	283.5	258.6	238.1	206.4	163.8	136.3	116.8	64.0	44.4	32.7
AVR95-27	2758.9	2519.4	2308.9	2128.7	1977.2	1732.7	1275.2	1015.6	848.5	643.3	521.0	440.4	383.4	340.7	307.2	280.1	258.0	223.6	177.5	147.7	126.6	69.4	48.1	35.4
AVR95-29	2971.1	2713.2	2486.5	2292.4	2129.3	1866.0	1373.3	1093.7	913.8	692.8	561.0	474.3	412.8	366.9	330.8	301.7	277.8	240.8	191.1	159.0	136.3	74.7	51.8	38.2
AVR95-31	3183.3	2907.0	2664.2	2456.2	2281.4	1999.3	1471.4	1171.9	979.0	742.3	601.1	508.2	442.3	393.1	354.4	323.2	297.6	258.0	204.8	170.4	146.0	80.1	55.5	40.9
AVR95-33	3395.5	3100.7	2841.8	2619.9	2433.5	2132.6	1569.5	1250.0	1044.3	791.8	641.2	542.0	471.8	419.3	378.1	344.8	317.5	275.2	218.4	181.7	155.8	85.4	59.2	43.6

Ratings in Watts at 77°F (25°C) to 1.80 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	570.9	524.9	484.5	446.8	416.2	366.7	278.0	224.7	189.8	145.2	118.3	100.3	87.5	77.8	70.3	64.1	59.1	51.3	40.7	33.9	29.1	15.9	11.1	8.14
AVR95-9	761.3	699.8	646.0	595.8	554.9	488.9	370.7	299.6	253.0	193.6	157.8	133.8	116.7	103.8	93.7	85.5	78.8	68.4	54.3	45.2	38.8	21.3	14.7	10.8
AVR95-11	951.6	874.8	807.6	744.7	693.6	611.1	463.3	374.5	316.3	242.0	197.2	167.2	145.9	129.7	117.1	106.9	98.5	85.5	67.9	56.5	48.5	26.6	18.4	13.6
AVR95-13	1141.9	1049.8	969.1	893.7	832.3	733.4	556.0	449.4	379.5	290.4	236.7	200.7	175.1	155.7	140.5	128.3	118.2	102.5	81.5	67.8	58.2	31.9	22.1	16.3
AVR95-15	1332.2	1224.7	1130.6	1042.6	971.0	855.6	648.6	524.3	442.8	338.8	276.1	234.1	204.2	181.6	164.0	149.6	138.0	119.6	95.1	79.1	67.8	37.2	25.8	19.0
AVR95-17	1522.5	1399.7	1292.1	1191.6	1109.7	977.8	741.3	599.2	506.1	387.2	315.5	267.6	233.4	207.6	187.4	171.0	157.7	136.7	108.7	90.5	77.5	42.5	29.5	21.7
AVR95-19	1712.8	1574.6	1453.6	1340.5	1248.5	1100.0	834.0	674.1	569.3	435.7	355.0	301.0	262.6	233.5	210.8	192.4	177.4	153.8	122.2	101.8	87.2	47.8	33.2	24.4
AVR95-21	1903.1	1749.6	1615.1	1489.5	1387.2	1222.3	926.6	749.0	632.6	484.1	394.4	334.5	291.8	259.5	234.2	213.8	197.1	170.9	135.8	113.1	96.9	53.1	36.8	27.1
AVR95-23	2093.4	1924.6	1776.6	1638.4	1525.9	1344.5	1019.3	823.9	695.8	532.5	433.9	367.9	320.9	285.4	257.7	235.2	216.8	188.0	149.4	124.4	106.6	58.4	40.5	29.8
AVR95-25	2283.8	2099.5	1938.1	1787.4	1664.6	1466.7	1112.0	898.8	759.1	580.9	473.3	401.4	350.1	311.4	281.1	256.5	236.5	205.1	163.0	135.7	116.3	63.8	44.2	32.5
AVR95-27	2474.1	2274.5	2099.7	1936.3	1803.3	1588.9	1204.6	973.6	822.3	629.3	512.8	434.8	379.3	337.3	304.5	277.9	256.2	222.2	176.6	147.0	126.0	69.1	47.9	35.3
AVR95-29	2664.4	2449.4	2261.2	2085.3	1942.1	1711.2	1297.3	1048.5	885.6	677.7	552.2	468.3	408.5	363.3	327.9	299.3	275.9	239.3	190.2	158.3	135.7	74.4	51.6	38.0
AVR95-31	2854.7	2624.4	2422.7	2234.2	2080.8	1833.4	1390.0	1123.4	948.8	726.1	591.6	501.7	437.6	389.2	351.4	320.7	295.6	256.4	203.7	169.6	145.4	79.7	55.3	40.7
AVR95-33	3045.0	2799.4	2584.2	2383.2	2219.5	1955.6	1482.6	1198.3	1012.1	774.5	631.1	535.2	466.8	415.2	374.8	342.1	315.3	273.4	217.3	180.9	155.1	85.0	59.0	43.4



SPACE SAVER™ SYSTEMS

AVR95 DISCHARGE RATES IN WATTS PER CELL *(cont.)*

Ratings in Watts per cell at 77°F (25°C) to 1.85 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	468.9	440.4	415.6	391.0	368.8	332.1	255.9	210.0	178.9	138.5	113.8	98.7	84.8	75.6	68.4	62.5	57.7	50.2	40.0	33.3	28.6	15.7	10.9	7.99
AVR95-9	625.2	587.1	554.1	521.3	491.7	442.8	341.2	280.0	238.5	184.7	151.7	131.5	113.1	100.8	91.2	83.4	77.0	66.9	53.3	44.4	38.1	20.9	14.5	10.6
AVR95-11	781.5	733.9	692.6	651.6	614.7	553.4	426.5	350.0	298.1	230.9	189.6	164.4	141.3	126.0	114.0	104.2	96.2	83.6	66.6	55.5	47.6	26.1	18.1	13.3
AVR95-13	937.8	880.7	831.1	781.9	737.6	664.1	511.8	419.9	357.7	277.0	227.6	197.3	169.6	151.2	136.8	125.1	115.5	100.4	79.9	66.6	57.1	31.3	21.7	16.0
AVR95-15	1094.1	1027.5	969.7	912.3	860.5	774.8	597.1	489.9	417.3	323.2	265.5	230.2	197.9	176.4	159.6	145.9	134.7	117.1	93.3	77.7	66.6	36.6	25.3	18.6
AVR95-17	1250.4	1174.3	1108.2	1042.6	983.5	885.5	682.5	559.9	477.0	369.4	303.4	263.1	226.1	201.6	182.4	166.8	154.0	133.8	106.6	88.8	76.1	41.8	28.9	21.3
AVR95-19	1406.7	1321.1	1246.7	1172.9	1106.4	996.2	767.8	629.9	536.6	415.5	341.3	296.0	254.4	226.8	205.2	187.6	173.2	150.5	119.9	99.9	85.7	47.0	32.6	24.0
AVR95-21	1563.0	1467.9	1385.2	1303.2	1229.3	1106.9	853.1	699.9	596.2	461.7	379.3	328.9	282.7	252.0	228.0	208.5	192.5	167.3	133.2	111.0	95.2	52.2	36.2	26.6
AVR95-23	1719.3	1614.6	1523.7	1433.6	1352.3	1217.6	938.4	769.9	655.8	507.9	417.2	361.7	310.9	277.2	250.8	229.3	211.7	184.0	146.6	122.1	104.7	57.5	39.8	29.3
AVR95-25	1875.6	1761.4	1662.3	1563.9	1475.2	1328.3	1023.7	839.9	715.5	554.0	455.1	394.6	339.2	302.4	273.6	250.2	231.0	200.7	159.9	133.2	114.2	62.7	43.4	31.9
AVR95-27	2031.9	1908.2	1800.8	1694.2	1598.2	1438.9	1109.0	909.9	775.1	600.2	493.0	427.5	367.5	327.6	296.4	271.0	250.2	217.4	173.2	144.3	123.7	67.9	47.0	34.6
AVR95-29	2188.2	2055.0	1939.3	1824.5	1721.1	1549.6	1194.3	979.9	834.7	646.4	531.0	460.4	395.7	352.8	319.2	291.9	269.4	234.2	186.5	155.4	133.3	73.1	50.7	37.3
AVR95-31	2344.5	2201.8	2077.8	1954.9	1844.0	1660.3	1279.6	1049.9	894.3	692.6	568.9	493.3	424.0	378.0	342.0	312.7	288.7	250.9	199.9	166.5	142.8	78.3	54.3	39.9
AVR95-33	2500.8	2348.6	2216.4	2085.2	1967.0	1771.0	1364.9	1119.8	953.9	738.7	606.8	526.2	452.3	403.2	364.8	333.6	307.9	267.6	213.2	177.6	152.3	83.6	57.9	42.6

Ratings in Watts per cell at 77°F (25°C) to 1.88 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	423.7	406.0	382.6	359.9	341.6	308.4	239.8	201.8	169.6	132.1	109.2	93.3	82.0	73.3	66.3	60.8	56.2	48.9	39.0	32.5	27.9	15.2	10.6	7.78
AVR95-9	565.0	541.3	510.2	479.8	455.4	411.2	319.8	269.1	226.1	176.1	145.5	124.5	109.3	97.7	88.5	81.1	74.9	65.2	52.0	43.3	37.1	20.3	14.1	10.4
AVR95-11	706.2	676.6	637.7	599.8	569.3	514.1	399.7	336.4	282.6	220.2	181.9	155.6	136.7	122.1	110.6	101.4	93.6	81.4	65.0	54.1	46.4	25.4	17.6	13.0
AVR95-13	847.5	812.0	765.3	719.7	683.2	616.9	479.6	403.7	339.1	264.2	218.3	186.7	164.0	146.5	132.7	121.6	112.3	97.7	78.0	65.0	55.7	30.5	21.2	15.6
AVR95-15	988.7	947.3	892.8	839.7	797.0	719.7	559.6	471.0	395.7	308.3	254.7	217.8	191.3	171.0	154.8	141.9	131.0	114.0	91.0	75.8	65.0	35.5	24.7	18.1
AVR95-17	1130.0	1082.6	1020.4	959.6	910.9	822.5	639.5	538.3	452.2	352.3	291.1	248.9	218.6	195.4	176.9	162.2	149.7	130.3	104.0	86.6	74.3	40.6	28.2	20.7
AVR95-19	1271.2	1218.0	1147.9	1079.6	1024.7	925.3	719.4	605.5	508.7	396.3	327.5	280.0	246.0	219.8	199.0	182.4	168.5	146.6	117.0	97.4	83.6	45.7	31.7	23.3
AVR95-21	1412.5	1353.3	1275.5	1199.5	1138.6	1028.1	799.4	672.8	565.2	440.4	363.8	311.2	273.3	244.2	221.1	202.7	187.2	162.9	130.0	108.3	92.8	50.8	35.3	25.9
AVR95-23	1553.7	1488.6	1403.0	1319.5	1252.5	1130.9	879.3	740.1	621.8	484.4	400.2	342.3	300.6	268.7	243.2	223.0	205.9	179.2	143.0	119.1	102.1	55.8	38.8	28.5
AVR95-25	1695.0	1623.9	1530.5	1439.4	1366.3	1233.7	959.3	807.4	678.3	528.4	436.6	373.4	328.0	293.1	265.4	243.3	224.6	195.5	156.0	129.9	111.4	60.9	42.3	31.1
AVR95-27	1836.2	1759.3	1658.1	1559.4	1480.2	1336.5	1039.2	874.7	734.8	572.5	473.0	404.5	355.3	317.5	287.5	263.5	243.3	211.8	168.9	140.7	120.7	66.0	45.8	33.7
AVR95-29	1977.5	1894.6	1785.6	1679.3	1594.0	1439.3	1119.1	942.0	791.3	616.5	509.4	435.6	382.6	341.9	309.6	283.8	262.0	228.1	181.9	151.6	130.0	71.1	49.4	36.3
AVR95-31	2118.7	2029.9	1913.2	1799.3	1707.9	1542.2	1199.1	1009.2	847.9	660.5	545.8	466.7	410.0	366.4	331.7	304.1	280.8	244.3	194.9	162.4	139.3	76.1	52.9	38.9
AVR95-33	2260.0	2165.2	2040.7	1919.2	1821.8	1645.0	1279.0	1076.5	904.4	704.6	582.2	497.9	437.3	390.8	353.8	324.3	299.5	260.6	207.9	173.2	148.6	81.2	56.4	41.5

Ratings in Watts per cell at 77°F (25°C) to 1.90 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	394.3	378.1	358.7	336.6	320.2	290.5	227.0	188.7	162.0	127.2	105.2	90.4	79.5	71.2	64.6	59.2	54.7	47.6	38.0	31.6	27.1	14.9	10.3	7.56
AVR95-9	525.7	504.1	478.3	448.7	427.0	387.4	302.7	251.6	215.9	169.6	140.3	120.6	106.0	95.0	86.1	78.9	73.0	63.4	50.6	42.2	36.2	19.8	13.7	10.1
AVR95-11	657.1	630.1	597.9	560.9	533.7	484.2	378.3	314.5	269.9	212.0	175.4	150.7	132.5	118.7	107.6	98.7	91.2	79.3	63.3	52.7	45.2	24.8	17.2	12.6
AVR95-13	788.5	756.2	717.5	673.1	640.5	581.0	454.0	377.4	323.9	254.4	210.5	180.8	159.0	142.4	129.1	118.4	109.4	95.2	75.9	63.3	54.3	29.7	20.6	15.1
AVR95-15	920.0	882.2	837.0	785.3	747.2	677.9	529.7	440.3	377.9	296.8	245.6	211.0	185.5	166.2	150.6	138.1	127.7	111.0	88.6	73.8	63.3	34.7	24.0	17.6
AVR95-17	1051.4	1008.2	956.6	897.5	853.9	774.7	605.3	503.2	431.9	339.2	280.7	241.1	212.0	189.9	172.2	157.9	145.9	126.9	101.2	84.4	72.4	39.7	27.4	20.2
AVR95-19	1182.8	1134.2	1076.2	1009.7	960.7	871.5	681.0	566.1	485.9	381.6	315.7	271.3	238.5	213.6	193.7	177.6	164.2	142.7	113.9	94.9	81.4	44.6	30.9	22.7
AVR95-21	1314.2	1260.3	1195.8	1121.9	1067.4	968.4	756.7	629.0	539.9	424.0	350.8	301.4	265.0	237.4	215.2	197.3	182.4	158.6	126.6	105.5	90.4	49.6	34.3	25.2
AVR95-23	1445.7	1386.3	1315.3	1234.1	1174.2	1065.2	832.3	691.9	593.8	466.4	385.9	331.5	291.5	261.1	236.7	217.0	200.6	174.5	139.2	116.0	99.5	54.5	37.7	27.7
AVR95-25	1577.1	1512.3	1434.9	1346.2	1280.9	1162.1	908.0	754.8	647.8	508.7	421.0	361.7	318.0	284.9	258.3	236.8	218.9	190.3	151.9	126.6	108.5	59.5	41.2	30.2
AVR95-27	1708.5	1638.4	1554.5	1458.4	1387.7	1258.9	983.7	817.7	701.8	551.1	456.1	391.8	344.6	308.6	279.8	256.5	237.1	206.2	164.5	137.1	117.6	64.4	44.6	32.8
AVR95-29	1839.9	1764.4	1674.1	1570.6	1494.4	1355.7	1059.3	880.6	755.8	593.5	491.2	422.0	371.1	332.3	301.3	276.2	255.4	222.1	177.2	147.7	126.6	69.4	48.0	35.3
AVR95-31	1971.4	1890.4	1793.7	1682.8	1601.1	1452.6	1135.0	943.6	809.8	635.9	526.2	452.1	397.6	356.1	322.8	296.0	273.6	237.9	189.8	158.2	135.7	74.4	51.5	37.8
AVR95-33	2102.8	2016.4	1913.2	1795.0	1707.9	1549.4	1210.7	1006.5	863.8	678.3	561.3	482.2	424.1	379.8	344.3	315.7	291.8	253.8	202.5	168.8	144.7	79.3	54.9	40.3



SPACE SAVER™ SYSTEMS

AVR95 DISCHARGE RATES IN WATTS PER CELL (cont.)

Ratings in Watts per cell at 77°F (25°C) to 1.94 v.p.c.

Cell Type	1 Min	5 Min	10 Min	15 Min	20 Min	30 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	7 Hr	8 Hr	9 Hr	10 Hr	12 Hr	16 Hr	20 Hr	24 Hr	48 Hr	72 Hr	100 Hr
AVR95-7	-	-	-	-	-	-	197.0	165.4	143.4	114.0	95.3	82.2	72.7	65.2	59.3	54.4	50.3	43.8	35.0	29.1	25.0	13.7	9.5	6.98
AVR95-9	-	-	-	-	-	-	262.6	220.5	191.2	152.0	127.1	109.7	96.9	87.0	79.0	72.5	67.0	58.4	46.6	38.8	33.3	18.3	12.7	9.30
AVR95-11	-	-	-	-	-	-	328.3	275.6	239.0	190.0	158.8	137.1	121.2	108.7	98.8	90.7	83.8	73.0	58.3	48.5	41.7	22.9	15.8	11.6
AVR95-13	-	-	-	-	-	-	394.0	330.7	286.8	228.0	190.6	164.5	145.4	130.5	118.5	108.8	100.5	87.6	69.9	58.2	50.0	27.5	19.0	14.0
AVR95-15	-	-	-	-	-	-	459.6	385.8	334.6	265.9	222.4	191.9	169.6	152.2	138.3	126.9	117.3	102.2	81.6	67.9	58.4	32.1	22.2	16.3
AVR95-17	-	-	-	-	-	-	525.3	441.0	382.4	303.9	254.1	219.3	193.9	174.0	158.0	145.1	134.1	116.8	93.3	77.6	66.7	36.6	25.3	18.6
AVR95-19	-	-	-	-	-	-	590.9	496.1	430.2	341.9	285.9	246.7	218.1	195.7	177.8	163.2	150.8	131.4	104.9	87.3	75.0	41.2	28.5	20.9
AVR95-21	-	-	-	-	-	-	656.6	551.2	478.0	379.9	317.7	274.1	242.3	217.4	197.6	181.3	167.6	146.0	116.6	97.0	83.4	45.8	31.6	23.3
AVR95-23	-	-	-	-	-	-	722.2	606.3	525.7	417.9	349.5	301.6	266.5	239.2	217.3	199.4	184.3	160.6	128.2	106.7	91.7	50.4	34.8	25.6
AVR95-25	-	-	-	-	-	-	787.9	661.5	573.5	455.9	381.2	329.0	290.8	260.9	237.1	217.6	201.1	175.2	139.9	116.5	100.0	55.0	38.0	27.9
AVR95-27	-	-	-	-	-	-	853.6	716.6	621.3	493.9	413.0	356.4	315.0	282.7	256.8	235.7	217.9	189.8	151.5	126.2	108.4	59.5	41.1	30.2
AVR95-29	-	-	-	-	-	-	919.2	771.7	669.1	531.9	444.8	383.8	339.2	304.4	276.6	253.8	234.6	204.3	163.2	135.9	116.7	64.1	44.3	32.6
AVR95-31	-	-	-	-	-	-	984.9	826.8	716.9	569.9	476.5	411.2	363.5	326.2	296.3	272.0	251.4	218.9	174.8	145.6	125.1	68.7	47.5	34.9
AVR95-33	-	-	-	-	-	-	1050.5	881.9	764.7	607.9	508.3	438.6	387.7	347.9	316.1	290.1	268.1	233.5	186.5	155.3	133.4	73.3	50.6	37.2

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 Phone: 610-682-6361 Fax: 610-682-4781

Order Department Hotline: 610-682-4231

www.eastpennunigy.com

E-mail: sales@eastpennunigy.com

E.P.M. Form No. 0975C Rev. 12/09
© 2009 by EPM Printed in U.S.A.

DISTRIBUTED BY:

All data subject to change without notice.
No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.